

ENGINE OPTIONS

The 12XC is available with Mitsubishi gas engine options in 49 or 74 horsepower. If your preference is diesel, Kohler 49 or 74 horsepower diesel engines are also offered. Depending on the engine, the drum is engaged by an auto or NACD spring-loaded clutch.

DIIRARI F DRIIM

A durable 20" diameter x 13 ¼" wide two-knife drum is standard with the fabricated components backed by a 5-year "GUTS" warranty. To assist with enhanced chipping throwing power, a slot called the "Power Slot" is located on the front side of the drum housing allowing for increased air flow or in the event of machine plugging significantly simplifying the unplugging process.



WIDE PROFILE INFEED

To simplify the feeding process, a wide profile 30 34" high x 54" wide infeed hopper with 30" fold down infeed pan is standard. The large infeed provides a robust platform for feeding multiple stems or brushy material at one time.



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178
FIND US ONLINE

FIND US ONLINE

WWW.BANDITCHIPPERS.COM

Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers
Horizontal Grinders • Attachments

SPECIFICATIONS

MEASUREMENTS	TOWABLE	
Length:	15' 11"	485.1 cm
Width:	6' 7"	200.7 cm
Height:	8' 4"	243.8 cm
Weight:	4,400 - 4,800 lbs.	1,995.8 - 2,177.2 kg
Engines:	49 - 74 HP (gas or diesel engine options)	
Fuel Tank:	18 gallon	68.1 L
Hydraulic Tank:	8 gallon	30.2 L

AXLE

Towable: (1) 7,000 lb. (3,175 kg) axle with electric brakes and (2) 235/80R 16" tires mounted on 8-bolt white modular rims

Standard & Custom Colors Available

Choose from two standard colors, or select a custom color to match your fleet.





FEED SYSTEM

A single 15 ¾" diameter top feed wheel with serrated feed wheel teeth driven by a 32.3 CID hydraulic motor enhances the chippers pulling capabilities. To assist with down pressure, two adjustable side mounted spring can generate over 700 pounds of down pressure reducing the need to trim or re-position material. For added down pressure a hydraulic lift cylinder is available as an option.



DIMENSIONS

Capacity: 12" 30.48 cm

Opening: 12 1/18" x 16 1/4" wide 30.8 cm x 41.3 cm wide

Drum: 20" diameter x 13 ¼" 50.8 cm x 33.02 cm wide wide – 2 knives

RPM: 1930

Lift Cylinder: Optional

Discharge: 360-degree manual swivel with 12" adjustable chip

deflector

Feed System: Pivot arm feed system with (2) 17" adjustable down pressure springs. Single 15 ¾" diameter x 15 7/8" wide top feed wheel powered by a 32.3 CID hydraulic motor

Frame: Mainframe is constructed of $\frac{1}{4}$ " x 2" x 4" rectangular

tubing with 3/8" x 3" x 6" tubular tongue

COMMITTED TO QUALITY & PRODUCTIVITY

Since 1983, Bandit has manufactured equipment for a multitude of wood waste processing markets. The vision since the beginning, is to build quality, highly productive, easy to maintain equipment providing years of dependable service.

The commitment for quality, innovation and dedication is instilled in every employee and is one of the main reasons why Bandit became an Employee-Owned Company (ESOP) in 2018. These core values ensure each Bandit machine will leave the factory ready to exceed your expectations.

DISCHARGE

The 12XC features a throw out the top discharge enhancing chip throwing power and gives the ability to discharge chips to the side if needed.



Bandit Offers a Complete Line of Tree Care Equipment:
Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers
Horizontal Grinders • Attachments